

DRASCOMBE GIG

SILAWAY SPECIFICATION

- ◆ GRP hull & decks. Laid up in polyester resin with gelcoat finishes, reinforced at strategic points with either additional lay-up or core-mat.
- ◆ Hull in white. Decks & aft locker hatch covers in light grey.
- ◆ Built in buoyancy of closed cell polyurethane foam in closed compartments with additional polystyrene block buoyancy in other areas.
- ◆ All the fitted hull joinery in Iroko, finished with Burgess woodsealer.
- ◆ Epoxy treated marine ply cockpit sole boards with non-slip finish.
- ◆ The hull has an Iroko keel plank & protective brass stemband.
- ◆ Full suit of terylene sails & set of varnished spruce spars.
- ◆ Jib is hanked on. Standing lug mainsail has three sets of reefing points. Mizzen has a boom.
- ◆ All required standing & running rigging, tubular sheethorse & traveller.
- ◆ Mastband is stainless steel. Standing rigging is 1 x 19 SS wire, talurit eye spliced.
- ◆ Galvanised steel centreplate & stainless steel winch lifting gear. Galvanised steel kick up rudder.
- ◆ Stemhead, tiller head, two mooring cleats, two pair rowlock sockets & pair of aft mooring fairleads in bronze.
- ◆ Tracks & blocks are by Barton.
- ◆ Other deck fittings are a combination of black nylon or stainless steel.
- ◆ Drain plug in aft of skeg.

She meets RCD regulations for Category C (coastal) for 12 adults.

There is a list of options on the price list but other items of equipment or special fit out can be introduced by discussion.

CBL reserve the right to modify this specification when required, up until the point that an order is placed.